

Revisions

| Issue | Date       | Note           |
|-------|------------|----------------|
| 1     | 12/07/2024 | See GTXPDC/971 |

USER INSTRUCTIONS



**User Instructions:**

Step 1: Open the cable stripper jaws (2), (3) and place the coaxial cable in position.

Step 2: Place your forefinger into the tool and rotate it around the cable as indicated by the arrow (1). Rotate approximately 5-6 times.

Step 3: Open the cable stripper jaws and inspect the results. Use the allen key provided to adjust the cassette blades (4) up or down as necessary.

Step 4: Repeat the process until the stripping tool is producing a satisfactory three stage strip, with a clean cut / finish on the braid, dielectric and centre core.

**Strip Dimension:**

A=8.0mm, B=4.0mm, C=4.0mm



|                    |                            |
|--------------------|----------------------------|
| 4                  | Allen key blade adjustment |
| 3                  | Blade Cassette             |
| 2                  | Press to open cable jaws   |
| 1                  | Direction of rotation      |
| <b>Information</b> |                            |

Unless otherwise specified tolerances  
 0.5-5 = ±0.2  
 >5-30 = ±0.4  
 >30-120 = ±0.6  
 >120-315 = ±1.0  
 >315-1000 = ±1.6  
 Angles = ±5°  
 Units = mm

This document is the confidential property of Gigatronix Limited and may not be copied, reproduced, modified or transmitted to any third party without written authorisation



|              |              |
|--------------|--------------|
| Author       | PJP          |
| Drawn By     | PJP          |
| Drawing date | 12/07/2024   |
| Checked by   | DB           |
| Checked date | 15/7/2024    |
| Scale        | Not to scale |

**Part Number** | GST-0322

**Title:** 3 Blade Stripping Tool for 12G SDI BNC Crimp Plugs